

# PRODUCT SPECIFICATIONS FOR DG150-2 (3 PHASE)

---

## GENERATOR SET SPECIFICATIONS

---

<b>Voltage</b>	480 Volts
<b>Frequency</b>	60 Hz
<b>Natural Gas/LPG Rating</b>	150 ekW / 140 ekW
<b>Emissions/Fuel Strategy</b>	U.S. EPA Certified for Stationary Emergency Application
<b>Speed</b>	1800 rpm
<b>Natural Gas Rating</b>	150 ekW / 140 ekW

---

## ENGINE SPECIFICATIONS

---

<b>Displacement</b>	535 in
<b>Engine Model</b>	8.8L V8, 4-cycle Gas
<b>Fuel System</b>	Natural Gas / LP Vapor
<b>Aspiration</b>	Turbocharged Air-to-Air Aftercooler
<b>Governor Type</b>	Electronic
<b>Compression Ratio</b>	10.1:1
<b>Bore</b>	4.35 in
<b>Stroke</b>	4.5 in

---

## GENERATOR SET DIMENSIONS

---

<b>Length</b>	119.6 in
<b>Width</b>	43.7 in
<b>Height</b>	65.2 in

.....

.....

## DG150-2 (3 PHASE) STANDARD EQUIPMENT

### AIR INLET

Single element air filter

### COOLING

Standard ambient temperatures up to 50°C (122°F)

Radiator and cooling fan complete with protective guards

### EXHAUST

Exhaust outlet with 2.5" pipe

### FUEL

Dual lock off valves

Natural Gas or LP Vapor

NPT connection

### GENERATOR

IP23 Protection

Matched to the performance and output characteristics of Cat engines

Integrated Voltage Regulator

### GOVERNOR

Electronic governor (non adjustable)

### CONTROL PANEL

EMCP 4.2 Series generator set controller

### MOUNTING

Rubber vibration isolators

### STARTING/CHARGING

12 volt starting motor

Batteries with rack and cables

## DG150-2 (3 PHASE) OPTIONAL EQUIPMENT

### GENERATOR

Anti-condensation heater

Excitation: [ ]Permanent Magnet Excited (PM)

Oversize and premium generators

#### STARTING/CHARGING

Battery charger – UL Listed 10 amp

Lube oil sump heater

Jacket water heater

Battery heater

#### GENERAL

Automatic transfer switches (ATS)

UL 2200 package

Suitable for Use as Service Equipment (SUSE)

CSA Certification

Enclosures: sound attenuated, weather protective