

PRODUCT SPECIFICATIONS FOR DG60-2 (3 PHASE)

GENERATOR SET SPECIFICATIONS

Voltage	480 Volts
Frequency	60 Hz
Natural Gas/LPG Rating	60 ekW / 60 ekW
Emissions/Fuel Strategy	U.S. EPA Certified for Stationary Emergency Application
Speed	1800 rpm
Natural Gas Rating	60 ekW / 60 ekW

ENGINE SPECIFICATIONS

Engine Model	5.7L V8, 4-cycle Gas
Displacement	350 in
Fuel System	Natural Gas / LP Vapor
Aspiration	Naturally Aspirated
Governor Type	Electronic
Compression Ratio	9.4:1
Bore	4 in
Stroke	3.48 in

GENERATOR SET DIMENSIONS

Length	83.3 in
Width	39.4 in
Height	53.5 in

.....

.....

DG60-2 (3 PHASE) STANDARD EQUIPMENT

AIR INLET

Single element air filter

COOLING

Radiator and cooling fan complete with protective guards

Standard ambient temperatures up to 50°C (122°F)

EXHAUST

Exhaust outlet with 3" pipe

FUEL

Natural Gas or LP Vapor

NPT connection

Dual lock off valves

GENERATOR

Integrated Voltage Regulator

IP23 Protection

Matched to the performance and output characteristics of Cat engines

GOVERNOR

Electronic governor (non adjustable)

CONTROL PANEL

EMCP 4.2 Series generator set controller

MOUNTING

Rubber vibration isolators

STARTING/CHARGING

12 volt starting motor

Batteries with rack and cables

DG60-2 (3 PHASE) OPTIONAL EQUIPMENT

GENERATOR

Anti-condensation heater

Excitation: []Permanent Magnet Excited (PM)

Oversize and premium generators

STARTING/CHARGING

Battery heater

Battery charger – UL Listed 10 amp

Jacket water heater

Lube oil sump heater

GENERAL

Suitable for Use as Service Equipment (SUSE)

UL 2200 Listed

Enclosures: sound attenuated, weather protective

CSA Certification

Automatic transfer switches (ATS)